



# C6 INLINE COUPLER UTP 50u



## Performance:

Meets C6 EIA/TIA 568B Standard.

## Materials:

Body : Fireproof ABS UL-94V0

Jack : 8P8C 50 micro inches gold plated

PCB : FR-4 / UL-94V0

## Electrical Specifications:

Insulation Resistance : 500M ohms (min.)

Contact Resistance : 20m ohms (max.)

Current Rating : 1.5 Amps .




DC Resistance : 0.1 ohms (max.)

Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

## Mechanical Specifications:

Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C




## Marking:

Cat. 6  
N3674  
KJ1

## Packing:

1 pcs / PE bag  
50 pcs / bag + label

|  |          |            |                             |           |
|--|----------|------------|-----------------------------|-----------|
| DRAW NO:   |          | ITEM NO:   |                             | DAILKJ-C6 |
|  APPR |          | CUSTOMER:  |                             |           |
| UNIT: m/m  | DESIGN   | DATE:      |                             |           |
| SCALE:   | Ref. NO: | TOLERANCE: | • ± 1 • X ± 0.2 • XX ± 0.15 |           |

# AMDEX